

553,774

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
4 November 2004 (04.11.2004)

PCT

(10) International Publication Number
WO 2004/095878 A2

- (51) International Patent Classification⁷: **H04R**
- (21) International Application Number:
PCT/US2004/012363
- (22) International Filing Date: 22 April 2004 (22.04.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/464,617 23 April 2003 (23.04.2003) US
- (71) Applicant (for all designated States except US): **RH LYON CORP** [US/US]; 691 Concord Avenue, Cambridge, MA 02139 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **LYON, Richard, H.** [US/US]; 60 Prentiss Lane, Belmont, MA 02478 (US). **BOWEN, David, L.** [US/US]; 19 Lancaster Street, Cambridge, MA 02140 (US). **UNGER, Gladys, L.** [US/US]; 28 Emerson Street, Belmont, MA 02478 (US).
- (74) Agent: **WEISSBURG, Steven, J.**; 238 Main Street, Suite 303, Cambridge, MA 02142 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND APPARATUS FOR SOUND TRANSDUCTION WITH MINIMAL INTERFERENCE FROM BACKGROUND NOISE AND MINIMAL LOCAL ACOUSTIC RADIATION



(57) Abstract: A transducer senses sounds produced by a talker or other source and measures acceleration of air. Enhancement of acceleration is accompanied by reduction of the portion of the sound energy that escapes from the regions around the transducer. The result is a high sensitivity transducer, with increased privacy for use in communication systems, especially cell phones and in a multi-person environment. A pressure sensor array with a weighted output is sensitive to sound from a source talker only, and not to acoustic background noise, and not to a local loudspeaker. The weighted signal is a source sum pressure signal. The array produces a signal (using a different weighing) that corresponds to an estimate of a derivative of pressure. The derivative signal is proportional to the volume velocity fluctuations produced by the source. This signal is enhanced, rather than reduced. A local loudspeaker is driven to make the source sum pressure signal as small as desired. The loudspeaker is driven to produce volume velocity fluctuations approximately equal and opposite to those produced by the source. No compression of air arises due to the talker, and no sound is radiated into the far field. All happens because the system is driven to reduce the source pressure sum signal to below a desired threshold. It is not necessary to directly measure the volume velocity fluctuations of the talker source.

WO 2004/095878 A2